

Résultat des mesures de rendement

Valeurs relevées

Freq	3,550	3,730	7,050	10,125	14,200	18,120	21,100	24,930	28,100	29,500
Double T	22	20	5	28	5	19	9	19	22	-18
S Match	19	20	10	28	0	17	8	18	20	13
Z Match ATF-S	15	28	19	29	1	18	2	20	22	19
Z Match II Tore	19	20	11	23	0	18	3	19	18	6
Transmatch 1:4	23	21	10	27	5	18	7	19	20	10
MFJ-962C	23	23	19	27	8	18	5	19	21	-20
0 => S9 20 => S9+20										
Center Feld 2x22,50m + 15,50m twin 450Ω										

Indication S	1	2	3	4	5	6	7	
Niveau reçu dBm	-121 dBm	-115 dBm	-109 dBm	-103 dBm	-97 dBm	-91 dBm	-85 dBm	
Indication S	8	9	+10dB	+20dB	+30dB	+40dB	+50dB	+60dB
Niveau reçu dBm	-79 dBm	-73 dBm	-63 dBm	-53 dBm	-43 dBm	-33 dBm	-23 dBm	-13 dBm

[Quelques infos sur les relations dBm, Watts, correspondances Vu-mètre http://radio.pagesperso-orange.fr/Math.htm](http://radio.pagesperso-orange.fr/Math.htm)

Rendement des Boites de Couplage, Antenne émission : Doublet Horizontal 2x23m

