

## Résultat des mesures de rendement

	3,550	3,730	7,050	10,125	14,200	18,120	21,100	24,930	28,100	29,500
Double T	32	31	33	22	24	32	37	13	30	6
S Match	22	22	33	23	27	30	36	18	22	4
Z Match ATF-S	20	18	33	20	23	30	37	15	28	-3
Z Match II Tore	33	33	32	20	27	30	36	18	27	5
Transmatch 1:4	22	20	32	23	22	31	37	18	29	5
MFJ	30	31	33	15	25	30	37	18	29	3
<b>0 =&gt; S9 20 =&gt; S9+20</b>										
Center Feld VERTICALE 2x6,35m + 15,50m twin 450Ω										

Indication S	1	2	3	4	5	6	7	
Niveau reçu dBm	-121 dBm	-115 dBm	-109 dBm	-103 dBm	-97 dBm	-91 dBm	-85 dBm	
Indication S	8	9	+10dB	+20dB	+30dB	+40dB	+50dB	+60dB
Niveau reçu dBm	-79 dBm	<b>-73 dBm</b>	-63 dBm	-53 dBm	-43 dBm	-33 dBm	-23 dBm	-13 dBm

Quelques infos sur les relations dBm, Watts, correspondances Vu-mètre <http://radio.pagesperso-orange.fr/Math.htm>

### Rendement des Boites de Couplage, Antenne émission : Doublet Horizontal 2x6,35m

